

(12) UK Patent Application (19) GB (11) 2 287 611 (13) A

(43) Date of A Publication 20.09.1995

(21) Application No 9505461.5

(22) Date of Filing 17.03.1995

(30) Priority Data

(31) 06049374 (32) 18.03.1994 (33) JP

(71) Applicant(s)

Fujitsu Limited

(Incorporated in Japan)

1015 Kamikodanaka, Nakahara-ku, Kawasaki-shi,  
Kanagawa 211, Japan

(72) Inventor(s)

Hideo Yunoki

(51) INT CL<sup>6</sup>

H04Q 3/00

(52) UK CL (Edition N)

H4K KF42 KOT

(56) Documents Cited

GB 2243517 A EP 0641133 A2 EP 0631457 A2

(58) Field of Search

UK CL (Edition N) H4K KF42 KOD3 KOT

INT CL<sup>6</sup> H04Q 3/00 11/04

ONLINE : WPI

(74) Agent and/or Address for Service

Haseltine Lake & Co

Hazlitt House, 28 Southampton Buildings, Chancery  
Lane, LONDON, WC2A 1AT, United Kingdom

(54) Multimedia communications systems

(57) In setting up a multimedia communication between terminals A, B involving a plurality of calls through different media, generating means, eg. at a service switching point 22, represent a call by generating "call objects" formed by connection points (CPs) connecting legs which correspond to the communications resources (physical or logical) assigned to a call request. CPs and legs are defined for each type of medium involved in the multimedia communication, and each CP is defined as a parent or child. A connection point generated at the time of a first call request is denoted as a parent CP; connection points subsequently generated in the same multimedia communication are denoted as child CPs. A multimedia communication involving a plurality of calls each requiring a different medium can be processed as a single "call object" by communications control means, eg. at a service control point 21, whereby a call processing load can be reduced. The processing is based on the relationship between connection points belonging to the same "call object". A process of charging an account on a multimedia call can be simplified by recording call history information for each connection point.




FIG. 3

GB 2 287 611 A




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5

6/15




FIG. 6

7/15

MULTI-MEDIA CALL OBJECT




FIG. 7






FIG. 8

9/15

SPECIFIC NUMBER  
CONVERSION TABLE

SPECIFIC NUMBER

CORRESPONDING DN

5

FIG. 9


10/15

CP ATTRIBUTE TABLE

CP	NO.
MAXIMUM THROUGHPUT	
TRANSMISSION QUALITY	
DIRECTIONAL FEATURE	

FIG. 10

FIG. 11







FIG. 12

## SCP PROCESS



## SSP PROCESS




FIG. 13

SCP PROCESS  
(SLP PROCESS)

## SSP PROCESS





FIG. 14



## SCP PROCESS



## SSP PROCESS




FIG. 15



## Multimedia Communications Systems

5           The present invention relates to multimedia communications systems which can provide communication through various media such as sound, graphics, animation, and text.

10       Description of the Related Art

          \_\_\_\_\_An intelligent network (IN) can\_\_\_\_\_ provide \_\_\_\_\_a system capable of developing a service application program independently of hardware by collectively managing, at a point in a network, service application programs conventionally provided for respective switching units.

          However, such a previously-considered IN includes only an integrated control procedure between a service control point (SCP) and a service switching point (SSP) in a specific communications network, and the control procedure among communications networks needs to be defined separately. That is, each communications network has its own control instructions, and therefore a program developed in an intelligent communications network cannot be used in another

20

25

intelligent communications network in the conventional IN system.

Desirably, an advanced intelligent networks (AIN) could be used to overcome such problems, in which a control procedure between the service control point and the service switching point is performed independently of communications networks.

As a result of the increasing amount of communications data that can be carried by a transmission line, following the introduction of optical cables, multimedia communications services have been presented lately which can provide various types of communication, using voice, graphics, animation, text, etc., simultaneously.

However, since communications using voice, graphics, animation, and text are processed as respective independent calls in currently used multimedia communications, a terminal user has to specify a receiving terminal unit for each communication medium, for example, a receiving terminal for voice data communication, a receiving terminal for graphic data communication, etc., thereby requiring complicated operations. Additionally, a switching unit in the current communications system performs call processing, such as setting and disconnecting a call, demanding an account, separately for each call even in

the multimedia communications by the same user. Thus, there arise a large number of call processing operations with a heavy load of processing on the switching unit.

5           It is desirable\_\_\_\_\_to simplify the operations performed by a terminal unit in multimedia communications and to reduce the process load in a communications network.

10           In a multimedia communications system embodying the present invention, for \_\_\_\_\_ performing communications using a plurality of media among a plurality of terminal units, an object generating unit generates an object which corresponds to a communications resource assigned to an individual  
15           communications request in multimedia communications, with the relation to other objects defined. It also generates an integrated object which integrates the plurality of objects.

20           A communications control unit integrally controls communications using a plurality of different media by managing a plurality of objects belonging to the same integral object generated by the object generating unit based on the relationships among the plurality of objects.

25           An intelligent network embodying the present

invention comprises a service control point for integrally controlling services provided in a communications network and a plurality of service switching points for accommodating a plurality of terminal units and processing calls among the terminal units. The service control point and the service switching point comprise the object generating unit and the communications control unit.

The object generating unit generates Legs corresponding to communications resources assigned to calls, for example, trunks, channels, etc. of an exchange, and connection points for connecting the Legs to one another. The connection point generated for the first call request is defined as a parent connection point, and connection points generated subsequently and related to the same multimedia call are defined as child connection points. It further generates a Call object for integrating the plurality of connection points and the plurality of the legs.

The communications control unit integrally controls a multimedia call containing a plurality of calls by managing the connection points and Legs based on the relationships among the plurality of connection points belonging to the same Call object.

An object may be generated by only a service

switching point, and a service control point can have the capability to process an object generated by the service switching point.

5 When a communications request is sent by a terminal unit, generated are an object which corresponds to the communications resource assigned to each communications request and defines the relation with other objects, and an integration object for integrating the plural objects. Since a plurality of  
10 calls are processed as a single multimedia call based on the relationship among the objects (for example, a parent-child relationship among connection points), a plurality of calls using different communications media can be integrally managed, thereby reducing the  
15 process loads in call processing on a multimedia communications network. Furthermore, since integrally processing a plurality of calls simplifies an operation at a call establishment and disconnection at a terminal unit, it also reduces a user's load.

20 Reference will now be made, by way of example, to the accompanying drawings, in which:

Figure 1 is a block diagram illustrating a general principle of an embodiment of the present invention;

25 Figure 2 is a block diagram illustrating the aforesaid general principle in more detail;

Figure 3 is a block diagram of the system configuration of an intelligent network embodying the present invention;

5. Figure 4 is a schematic diagram of a service control point;

Figure 5 is a schematic diagram of a service switching point;

10 Figure 6 is a schematic diagram illustrating an AIN call model;

Figure 7 is a schematic diagram illustrating a multimedia Call object;

Figure 8 is a diagram illustrating a configuration of a Call-related table and a CP-related table;

15 Figure 9 is a diagram illustrating a configuration of specific number conversion table;


Figure 10 is a diagram illustrating a configuration of a CP attribute table;

Figure 11 is a diagram showing signaling flow;

20 Figure 12 is a diagram illustrating a configuration of a center DB; and

Figures 13 to 15 are flowcharts showing the operation of a service control point and a service  
25 switching point.

Figure 1 is a block diagram showing the general principle of an embodiment of the present invention. In a multimedia communications system in which  
30 communications are established using a plurality of media among a





plurality of terminal units, an object generating unit 1 generates an object defined as being associated with other objects corresponding to communications resources assigned to each communications request in the multimedia communications. It also generates an integration object to integrate a plurality of generated objects.

A communications control unit 2 collectively controls communications of different media by controlling the objects based on the relationships among the plural objects belonging to the same integration object generated by the object generating unit 1.

Figure 2 is a block diagram showing a principle of the system configuration of an intelligent communications network embodying the present invention.

The intelligent network comprises a service control point 3 for collectively controlling a service provided in a communications network; and a service switching point 4 for accommodating a plurality of terminal units and processing calls among the terminal units. Each of the service control point 3 and the service switching point 4 comprises the object generating unit 1 and the communications control unit

2.

The object generating unit 1 generates Legs which are objects corresponding to the communications resources, such as trunks, channels, etc. of a switching unit, and connection points, which are objects connecting the Legs. It defines the connection point generated for the first call request as a parent connection point; and connection points subsequently generated for the same multimedia call as child connection points. The object generating unit 1 also generates a Call object for integrating the connection points and the Legs.

The communications control unit 2 collectively controls a multimedia call containing a plurality of calls by managing connection points and Legs based on the relationships among plural connection points belonging to the same call object. An embodiment of the present invention can also be designed such that the objects are generated by the service switching point 4 only, and the service control point 3 processes the objects generated by the service switching point 4.

In an embodiment of the present invention, an object is generated which is associated with other objects and corresponds to communications resources assigned to each communications request of multimedia communication; and an integration object for



integrating of the objects when a request for multimedia communications is issued by a terminal unit. Then, a plurality of calls are processed as a single multimedia call based on the relationship among the objects (for example, a relationship between a parent connection point and a child connection point, etc.). Thus, a plurality of calls of different communications media can be collectively managed, thereby reducing a load required in call processing in the communications network in which multimedia communications are provided. Furthermore, an integral processing of a plurality of calls simplifies an operation performed to establish or disconnect a call and therefore reduces the load on the user.

— Embodiments of the present invention are described below by referring to the attached drawings. Figure 3 shows the configuration of an advanced intelligent network system (hereinafter referred to as an AIN) in a — multimedia communications system embodying the present invention. The AIN is shown in use — in an asynchronous transfer mode (ATM) switching network.

In Figure 3, a service control point (SCP) 21 is a control device for processing subscriber

information, controlling a data base, etc. and is provided with an integral data base containing subscriber information, network configuration information, service application programs, etc. together with a function of performing a communications process, providing services, etc.

A service switching point (SSP) 22 is an ATM switching unit, transmits a service request from a subscriber to the service control point 21, and controls a communications network according to the instruction of the service control point 21.

A plurality of the service switching points 22 can be connected to the service control point 21 and a control signal is transmitted between the service control point 21 and the service switching point 22 through a common channel signaling #7.

Multimedia terminal units A and B, a plurality of terminal units not shown in Figure 3, and an image providing center 23 are connected to the service switching point 22. The image providing center 23 is connected to the service switching point 22 via an optical fiber subscriber line.

The configurations of the above service control point 21 and service switching point 22 are described below by referring to Figures 4 and 5 respectively.

The service control point 21 comprises a processor (CC) 31; a memory (MM) 32 for storing an advanced intelligent network call model (described later) processing program, a service control program, etc.; a hard disk (HD) 33 for storing subscriber information, a service application program, etc.; and a protocol handler (SS7 handler) 34 for performing an inter-work with the service switching point 22 through the common channel signaling #7 as shown in Figure 4.

As shown in Figure 5, the service switching point 22 comprises an ATM switch (ATM-SW) 41 having an ATM switching function; a processor (CC) 42 for processing a call; a memory (MM) 43 for storing a control program for an AIN; a hard disk 44; and an SS7 handler 45 for protocol conversion between the protocol of the common channel signaling #7 and an ATM-SM internal protocol.

The advanced intelligent network call model (hereinafter referred to as an AIN call model) is described below by referring to Figures 6 and 7.

In a multimedia communications service, if a call request is issued by a subscriber terminal unit, the service switching point 22 generates an object consisting of a connection point (CP) and a Leg, corresponding to communications resources (physical or logical resources) assigned to the call request, and

then generates a single Call object in response to a single multimedia call.

Figure 6 shows the relation among objects. CP1 and CP2 indicate connection points, and Legs are connected to both ends of blocks corresponding to connection points CP1 and CP2. The objects are included in the Call object.

A Leg is an object indicating an input/output of communications, and is generated corresponding to physical resources such as a trunk, subscriber line and logical resources such as a channel, etc. A connection point (CP) is an object connecting the Legs. In the service switching point 22 and the service control point 21, a call is defined using a connection point and a Leg, and is controlled between the service switching point 22 and the service control point 21 based on the objects.

Then, a call reference number (CRNO) is assigned to the first call request in a single multimedia communication, and a connection point generated at this time is defined as a parent CP, and connection points generated subsequently with the same call reference number are associated with the parent CP as child CPs.

For example, if terminal A shown in Figure 3

issues the first call request to terminal B in a multimedia communications service, the service switching point 22 generates a Leg corresponding to a path to terminal A (for example, Leg No.1), a Leg corresponding to a path to terminal B (for example, Leg No.2), and a parent connection point CP1 connecting the Legs. Simultaneously, a Call object containing the Legs and CP1 is generated.

Then, when a path (for example, a path for use in text communication) is established between terminal B and the image providing center 23, the service switching point 22 generates a Leg corresponding to a path to terminal B, a Leg corresponding to a path to the image providing center 23, and a connection point connecting the Legs. The connection point generated at this time is associated as a child connection point CP2 with the already generated parent CP1, and as a part of the Call object containing the parent CP1.

If another path (for example, a graphics communications path) is set between the image providing center 23 and terminals A and B, then the service switching point 22 generates a Leg corresponding to a path to the image providing center 23, a Leg corresponding to a path to terminal B, a Leg corresponding to a path to terminal A, and a

connection point connecting the Legs. The connection point generated at this time is associated as a child connection point CP3 with the already generated parent CP1, and is associated as a part of the Call object.

5        Figure 7 shows the multimedia Call object indicating the relationship between the parent CP1 and the child CPs 2 and 3. In the multimedia communications, the connection point for the first call is generated as a parent CP, and the connection  
10       points generated subsequently for the same multimedia call are associated as the child CPs with the parent CP. The entire multimedia call are managed by a Call object. The Call object is generated and deleted by a parent CP.

15       Thus, representing a plurality of calls of different media in the multimedia communications by a Leg and a connection point makes it possible to define the relationship between a call and communications  
20       resources in a communications network independently of the instruction system of the network. Furthermore, associating the connection points of a plurality of calls in a single multimedia communication with each  
25       other and processing them as a single Call object enables the plural calls of different media to be processed collectively.



\_\_\_\_\_In the present embodiment, a call is set for each communications media, and a connection point is generated for each call correspondingly. The first generated connection point in the plural connection points is defined as a parent CP and the subsequently generated connection points having the same call reference number are associated with the parent CP as child CPs. The parent CP and the child CPs have following features.

A multimedia call can be disconnected (all connection points can be released) only from a terminal unit connected to a Leg of the parent CP. Entire call cannot be disconnected (a Call object cannot be released) from a terminal unit which is connected to a Leg of the child CP. The terminal can release its own connection point only. If a Leg of the parent CP issues a request to disconnect an individual CP, not a request to disconnect a multimedia call, then physical resources (circuits, channels, etc.) concerning the parent CP can be released, but virtual resources such as Legs and CP attributes in a call-related table and a CP-related table (described later) are not deleted.

Since the Leg information [a Leg number, a directory number (DN)(terminal unit designation

number)] of the parent CP can be used as a directory number when a child CP is generated, an entry operation of a directory number can be omitted for the same directory number.

5        Then, the configurations of the Call-related table and the CP-related table generated in the service control point 21 and the service switching point 22 are described below by referring to Figure 8.

10        For example, if a call request is issued with a specific number (for example, a free-charge dial number) designated as a destination directory number, then the service switching point 22 transmits the specific number to the service control point 21. Simultaneously, the service switching point 22  
15        generates a connection point and a Leg in response to the call request, assigns them a parent CP number and a Leg number (Leg No.), and transmits them together with a source directory number, a media type, etc. to the service control point 21.

20        Upon receipt of the data of a specific number, the service control point 21 activates a service logic program (SLP), refers to the specific number conversion table shown in Figure 9 through the service logic program, converts the designated specific number  
25        data into a corresponding destination directory



number, and transmits the destination directory number to the service switching point 22.

5 The service control point 21 and the service switching point 22 generates the Call-related table, the CLRD field, and the CP-related table shown in Figure 8, and the CP attribute table shown in Figure 10, enters the correspondence information of CPs into the tables, and enters the destination directory number corresponding to a CP number and a Leg number  
10 into the tables.

The Call-related table shown in Figure 8 stores a call reference number (CALLNO.), a parent CP number, the number of child CPs (Number of Child\_CP) and child CP numbers (Child\_CPNO) if there is any child  
15 CPs, and a header address of the Call Record (CLRD) field storing call history information. The CLRD field stores, for each CP, call history information such as a connection date, a disconnection date, a communication time, a communications throughput, and  
20 media, etc.

The CP-related table stores, for each CP, data such as a CP number, a CP attribute, the number of Legs, data indicating the correspondence between a Leg number and a directory number. The CP attribute  
25 includes a media type, the maximum throughput of

communications, a band, a transmission quality (loss of cells, etc.), a parent CP flag (indication as to whether or not it is a parent CP), a related Call number, the communications directional feature (one-way or two-way), etc.

The CP attribute table shown in Figure 10 stores data such as a CP number, the maximum throughput of communications, a transmission quality, and data indicating the communications directional feature.

Assuming that a multimedia real estate sales support service is provided for the IN shown in Figure 3, the control operation between the service control point 21 and the service switching point 22 is described below by referring to the signaling flowchart shown in Figure 11. A telephone call is made from multimedia terminal unit A to terminal unit B of real estate agent to obtain the video information about real estate sent from the image providing center (video center) 23.

When a specific number is accessed by terminal unit A (Figure 11(1)), the service switching point 22 assigns to the call request a call reference number (CR) for identifying the call, a CP number (CP1), a Leg number. These data are added to a "call org" message [Call org (CR, CP1)] and transmitted to the

service control point 21 (Figure 11 (2)). CP1 is a CP number assigned to a parent CP.

Upon receipt of the call request message having a specific number, the service control point 21  
5 activates a service logic program (SLP), converts the specific number into a corresponding directory number, and transmits the response message having the directory number [Connect (CR, CP1, DN) to the service switching point 22 (Figure 11(3)).

10 Since the service switching point 22 recognizes according to the destination directory number in the response message that the destination terminal unit is terminal unit B, the call is transmitted to terminal B of the real restate agent (Figure 11(4)). At this  
15 time, the service switching point 22 notifies terminal B of the call reference number (CR) assigned to the call from terminal A.

If terminal B is ready to respond, a path is established between terminal A and terminal B. In  
20 Figure 11, the solid line 110 connecting terminal A to terminal B indicates the path established between them. CP1 and two Legs connected to CP1 at the position of an SSP on the path are a connection point and Legs generated by the service switching point 22  
25 corresponding to the communications resources of the

path established between terminals A and B.

When button A of terminal unit B is depressed, a call request message having the call reference number of the call received from terminal A is transmitted from terminal B to the service switching point 22 accommodating terminal B (Figure 11(5)). At this time, terminal B transmits the video title to be displayed on terminal A and the information about the TV system of terminal A (HDTV or Normal TV), which is designated by terminal A, with the call request message.

Upon receipt of the call request message from terminal B, the service switching point 22 recognizes according to the call reference number added to the message that the request to set a call requests to generate a child CP of CP1 (parent CP). Accordingly, the CP number "CP2" assigned to the generated connection point is entered as the child CP number (Child\_CPNO.) of CP1 into the Call-related table shown in Figure 8. Thus, one child CP is set and the number of Child CPs in the Call-related table is set to 1. Then, CP2 is entered as a CP number (CP NO.) into the CP-related table, and the CP attribute, the number of Legs, and the Leg number/directory number of CP2 are entered.

Upon entering CP2 as a child CP of parent CP1 into the Call-related table, the service switching point 22 transmits to the service control point 21 a "Call Org" message [Call Org (CR, CP2)] having the call reference number and CP2 (Figure 11(5')).

Like the service switching point 22, the service control point 21 updates the Call-related table, the CP-related table, etc. according to the received information, and then searches the data base about the image providing center 23 with the video title and the TV system specified by terminal unit B to retrieve the directory number of an appropriate center. Then, a "Connect" message provided with the retrieved directory number of the center is transmitted to the service switching point 22 (Figure 11(6)). If a plurality of centers can be detected when the directory number is retrieved, then the service control point 21 provides an access pointer for pointing to a center on the secondary table shown in Figure 12. Then, the directory number of the video center pointed to by the access pointer is selected. Additionally obtained is the specific information (video unit number, etc.) of the selected video center from the third table. After the selection of the video center, the value of the access pointer is

incremented by 1. Thus, selecting a video center using the access pointer enables all video centers to be equally accessed even if a plurality of video centers exist.

5        If the directory number of a video center has been specified, the service switching point 22 transmits to the image providing center 23 an arrival message with the specified directory number as a destination directory number (Figure 11(7)). Thus, a  
10       text communications path is established between terminal B and the image providing center 23.

      In Figure 11, the solid line 111 connecting terminal B and a video center indicates the text communications path established between them. CP2 and  
15       two Legs connected to CP2 at the position of an SSP on the path are a connection point and Legs corresponding to the communications resources of the path established between terminal B and a video center. CP1 and two Legs connected to CP1 are a CP and Legs  
20       corresponding to the communications resources of the path established between terminals A and B as described above.

      If the text communications path has been established between terminal B and the video center,  
25       then terminal B specifies the start of a video



broadcast by designating one of the normal replay, a high-speed replay, and a slow replay via the text communications path (Figure 11(8)).

5 Then, the video center transmits to the service switching point 22 a SETUP message containing the call reference number specified by a call from terminal B so as to start the video broadcast. In this case, required media is animation.

10 If the service switching point 22 determines that the call setting request is a request to set a child CP based on the call reference number of the received SETUP message, then it assigns CP3 as a CP number to the call setting request, adds the call reference number, a Leg number, and a CP number to the call  
15 origination message [Call org (CR, CP3)], and transmits it to the service control point 21 (Figure 11 (10)).

20 The service switching point 22 retrieves the Call-related table using the call reference number and enters CP3 into the table as a child CP of the parent CP which has the same call reference number. Since two child CPs 2 and 3 have been entered for CP1, the "Number of Child\_CP's" of the call-related table is set to 2.

25 After entering the data of CP2 into the CP-

related table, entered are the CP attribute, the number of Legs, the Leg number/directory number of CP3. Since the media required by the video center is animation, the media field of the CP attribute in the CP-related table is set to animation.

The service control point 21 updates the Call-related table, the CP-related table, etc. based on the information from the service switching point 22, extracts the Leg number of CP1, that is, the parent CP of CP3, from the Call-related table and transmits it to the service switching point 22 with the Leg number of CP1 added to the "Connect" message [Connect (CR, CP3, CP1 Leg NO.))(Figure 11(11)).

Upon receipt of the "Connect" message specifying CP3 and the Leg numbers of CP1 from the service control point 21, the service switching point 22 sends an arrival message to the terminal units specified by CP3, CP1 and the respective Leg numbers, that is, terminals A and B (Figure 11(12)).

Thus, an animation communications path is established between the video center and terminal unit A and between the video center and terminal unit B, thereby starting a video broadcast (Figure 11(13)).

In Figure 11, the solid line 112 connecting terminals A and B and a video center indicates the



animation communications path established among them.  
CP3 and three Legs connected to CP3 at the position of  
an SSP on the path are a connection point and Legs  
corresponding to the communications resources of the  
5 path established among the video center, terminals A  
and B. CP2 and two Legs connected to CP2 correspond  
to the communications resources of the path between  
the video center and terminal B. CP1 and two Legs  
connected to CP1 are a CP and Legs corresponding to  
10 the communications resources of the path established  
between terminals A and B.

The broken lines connecting CP1, CP2, and CP3  
indicate that these connection points have a parent-  
child relationship with CP1 defined as a parent and  
CP2 and CP3 as children, and that these connection  
15 points and the Legs form a call object.

Terminal B can perform a video operation on the  
picture provided by the video center. For example, if  
terminal B issues a video operation instruction for  
20 fast forwarding, then the instruction is transmitted  
to the video center via the communications path of  
CP2, that is, the text communications path 111  
established between terminal B and the video center  
(Figure 11(14)).

25 If a user of terminal A depresses a call

disconnection button to terminate the video broadcast of real estate information, then a "Call Clear" message [Call Clear (CR, CP1)] having the parameters of the call reference number and CP1 is issued from terminal A to the service switching point 22 (Figure 11(15)). If the service switching point 22 determines according to, the call reference number added to the "Call Clear" message, that the instruction is a request to disconnect the entire multimedia call, then it refers to the Call-related table to confirm that CP1 is the parent CP with the call reference number, and releases the data relating to the call reference number in the Call-related table and the CP-related table (virtual resources) and the physical resources. Furthermore, the service switching point 22 notifies the service control point 21 that the call with the call reference number is disconnected. Upon receipt of the disconnection information about the multimedia call, the service control point 21 stores into the hard disk the call history information for each CP in the CLRD field specified in the Call-related table.

The call history information stored in the CLRD field includes date and time of a connection, date and time of a disconnection, communications time, applied throughput, transmission quality, media, number of

packet segments, added service information, the number of Legs of each CP, etc. The service control point 21 can perform an accounting process for each CP or for the entire multimedia call according to the call history information.

If a user of terminal A terminates only a part of a multimedia call, for example, voice communications by setting the telephone with its receiver on the hook, then an individual disconnection request message of CP1 is transmitted from terminal A to the service switching point 22. The service switching point 22 releases only the physical resources related to CP1 in response to the CP individual disconnection request, but does not release the virtual resources associated with the Call object including CP1 in the Call-related table and the CP-related table. Thus, only the voice communications are terminated while the animation and text communications continue.

Figure 13 is a flowchart showing the operations of the service control point (SCP) 21 and the service switching point (SSP) 22 performed when a special number is accessed by terminal A. Upon receipt of the access to a special number from terminal A (S1), the service switching point 22 assigns to the call request a call reference number (CR), a CP number, and a Leg

number (S2), adds these information to the call origination message (CALL ORG MSG), and sends it to the SCP 21 (S3).

When the SCP 21 receives the CALL ORG MSG (S4),  
5 it activates a service logic program (SLP) (S5), and converts the specified special number into a corresponding directory number (S6). Then, it sends to the SSP 22 a response message (CONNECT MSG) provided with the directory number (S7).

10 Then, the SCP 21 generates a Call related table, a CP related table, and a CP attribute table as shown in Figures 8 and 10, and enters related data into the tables (S8).

When the SSP 22 receives the response message  
15 sent from the SCP 21 in S7 (S9), it also generates a Call related table, a CP related table, and a CP attribute table as with the SCP 21, and enters related data into the tables (S10). Then, it sends the call to the terminal specified by the directory number  
20 added to the received response message (S11).

Figure 14 is a flowchart showing the operation of the SCP 21 and the SSP 22 performed when the button A of terminal B is pressed.

When the SSP 22 receives from terminal B a call  
25 request message caused by the press of the button

(S20), it is determined whether or not the CR added to the message has been entered into the Call related table (S21). If it is determined that the CR has been entered into the Call related table (yes in S21), then  
5 the call set request can be recognized as a request for the generation of a child connection point. Therefore, the CP number assigned to the generated connection point is entered as a child CP into the Call related table. Thus, one child CP has been set,  
10 and the number of child CPs in the call related table is set to 1. Then, CP2 is entered as the CP number (CP No.) into the CP related table, and the CP attribute, the number of Legs, and the Leg number/directory number of CP2 are set (S22).

15 After the SSP 22 has entered CP2 as a child CP of the parent CP1 into the Call related table, it sends to the SCP 21 a CALL ORG MSG provided with a CR and CP number (S23).

20 If it is determined by the SSP 22 in S21 that the CR is not entered into the Call related table (no in S21), then the request is not for generating a child connection point and SSP 22 performs a normal call process (S24).

25 Upon receipt of the CALL ORG MSG sent from the SSP 22 in S23 (S25), the SCP 21 updates the Call

related table, the CP related table, etc. according to the received information as with the SSP 22 (S26). Then, the data base about the image providing center 23 is searched for a directory number of an operable  
5 image providing center based on the information specified by terminal B (S27). Then, a CONNECT MSG provided with the directory number of the detected center is transmitted to the SSP 22 (S28).

When the SSP 22 receives the CONNECT MSG  
10 transmitted from the SCP 21 (S29), it transmits to the video center 23 a message using the directory number attached to the CONNECT MSG as a destination directory number (S30).

Figure 15 is a flowchart showing the operations  
15 of the SCP 21 and the SSP 22 performed when a user of terminal A presses a call disconnection button to terminate a video broadcast of real estate information.

The SSP 22 receives from terminal A a call clear  
20 message (CALL CLEAR MSG) having parameters of CR and CP1 (S40). If the SSP 22 determines according to the parameter of a CR, etc. added to the CALL CLEAR MSG that a request for disconnecting an entire multimedia call has been issued, then it further determines  
25 whether or not the CP which issued the request is a



parent CP by referring to the Call related table (S41).

5 If it is determined that the CP is a parent CP (yes in S41), then released are the physical resources and the data related to the CR in the Call related table, the CP related table, and the CP attribute table (virtual resources) (S42). Then, call history information for each CP is stored into the hard disk from a CLRD field specified in the Call related table  
10 (S43). The disconnection of a call with the CR is reported to the SCP 21 (S44).

If the SSP 22 determines that the CP is not a parent CP in S41 (no in S41), then the SSP 22 rejects the request for disconnecting an entire multimedia  
15 call (S45).

Upon receipt of the disconnection information about the multimedia call sent from the SSP 22 in S44 (S46), the SCP 21, as with the SSP 22, releases the physical resources and the data related to the CR in  
20 the Call related table, the CP related table, and the CP attribute table (virtual resources) (S47). Then, call history information for each CP is stored into the hard disk from a CLRD field specified in the Call related table (S48).

25 In the multimedia communications using plural



types of media including voice, animation, and text according to the above described embodiment, CPs and Legs are defined for each type of media and each CP is defined as a parent or a child. Thus, a plurality of  
5 calls, each requiring different media, can be processed as a single Call object and therefore a load in a call processing can be reduced in the service control point 21 and the service switching point 22 more than in the case where a plurality of calls of  
10 different media are processed separately. Furthermore, recording call history information for each connection point simplifies a process of charging an account on a multimedia call. Furthermore, collectively processing a plurality of calls as a  
15 single multimedia call prevents a user from repeating the same operation for each call, thereby reducing user entry operations.

The above described embodiment of the present invention is described in use in an intelligent  
20 network in an ATM switching network. However, embodiments of the present invention is not limited to this application, but can be applied to multimedia communications among terminal units connected to other switching network or a computer network having no switching function. Furthermore, embodiments may be used in a communications

network other than an advanced intelligent network.

5

10

15

20

25

## CLAIMS:

1. A multimedia communications system in which terminal units communicate with each other through a plurality of media, comprising:

5 object generating means (1) for generating an object which defines a relationship with other objects and corresponds to communications resources assigned to a communications request in a multimedia communication, and for generating an integral object  
10 for managing a plurality of objects; and

communications control means (2) for collectively controlling communications through different media by managing a plurality of objects belonging to a same  
15 integral object generated by said object generating means (1) based on a relationship between the plurality of objects.

2. The multimedia communications system according to claim 1, wherein  
20

said multimedia communications system is an intelligent network system;

said object generating means (1) generates, when a call request is issued, an object comprising Legs  
25 corresponding to communications resources assigned for

a call and a connection point which connect the Legs,  
said connection point generated for a first call  
request being defined as a parent connection point,  
said connection point subsequently generated for a  
5 same multimedia call being defined as a child  
connection point, and generates a Call object for  
integrating the parent connection point and its Legs  
and the child connection points and its Legs; and

said communications control means (2)  
10 collectively controls a plurality of calls based on  
the relationship among the connection points belonging  
to a same Call object.

3. The multimedia communications system according to  
15 claim 2, wherein

said object generating means (1) assigns a call  
reference number to the first call request from a  
terminal unit, generates the parent connection point  
and the Leg corresponding to the communications  
20 resources assigned to the first call, generates the  
child connection points and the Legs corresponding to  
the communications resources assigned to the call  
requests subsequently generated, and generates a Call  
object for integrating a plurality of connection  
25 points having a same call reference number and the

Legs.

4. The multimedia communications system according to claim 2, wherein

5        said communications control means (2) disconnects  
a multimedia call by releasing the plurality of  
connection points and the Legs belonging to the Call  
object only if a terminal unit having the parent  
connection point has issued a request to release the  
10 call object, and disconnects the call individually by  
releasing a connection point and a Leg specified by a  
request for an individual release if a terminal unit  
having the parent or child connection point has issued  
the request for the individual release.

15

5. The multimedia communications system according to claim 2, wherein

      said object generating means (1) comprises:

      first storing means for storing information  
20 which indicates a correspondence between the parent  
connection point and the child connection point; and

      second storing means for storing information  
which indicates a correspondence between a Leg number of  
each connection point and a terminal unit  
25 specification number in a communications network; and

said communications control means (2) collectively controls a multimedia call according to the information stored in said first storing means and the information stored in said second storing means.

5

6. The multimedia communications system according to claim 3, wherein

said communications control means (2) disconnects a multimedia call by releasing the plurality of connection points and the Legs belonging to the Call object only if a terminal unit having the parent connection point has issued a request to release the call object, and disconnects the call individually by releasing a connection point and a Leg specified by a request for an individual release if a terminal unit having the parent or child connection point has issued the request for the individual release.

10

15

20

7. The multimedia communications system according to claim 3, wherein

said object generating means (1) comprises:

first storing means for storing information which indicates a correspondence between the parent connection point and the child connection point; and

25

second storing means for storing information

which indicates a correspondence between a Leg number of each connection point and a terminal unit specification number in a communications network; and

5       said communications control means (2) collectively controls a multimedia call according to the information stored in said first storing means and the information stored in said second storing means.

8.   The multimedia communications system according to  
10   claim 4, wherein

      said communications control means (2) releases only physical resources for the connection point if a terminal unit has issued a request to individually release the connection point, and does not release  
15   virtual resources related to the Call object.

9.   The multimedia communications system according to claim 6, wherein

      said object generating means (1) comprises:

20       first storing means for storing information which indicates a correspondence between the parent connection point and the child connection point; and

      second storing means for storing information which indicates a correspondence between a Leg number of  
25   each connection point and a terminal unit



specification number in a communications network; and

5       said communications control means (2) collectively controls a multimedia call according to the information stored in said first storing means and the information stored in said second storing means.

10.   The multimedia communications system according to claim 6, wherein

10       said communications control means (2) releases only physical resources for the connection point if a terminal unit has issued a request to individually release the connection point, and does not release virtual resources related to the Call object.

15   11.   The multimedia communications system according to claim 7, wherein

20       said first storing means stores a call reference number for use in identifying a multimedia call, a parent connection point number, a child connection point number, and call history information for each connection point;

25       said second storing means stores at least a connection point number, a media type, a maximum communications throughput, and information indicating a correspondence between a Leg number and a terminal

unit specification number; and

5       said communications control means (2) charges an account on the multimedia call based on the call history information for each connection point stored in said first storing means.

12. The multimedia communications system according to claim 9, wherein

10       said first storing means stores a call reference number for use in identifying a multimedia call, a parent connection point number, a child connection point number, and call history information for each connection point;

15       said second storing means stores at least a connection point number, a media type, a maximum communications throughput, and information indicating a correspondence between a Leg number and a terminal unit specification number; and

20       said communications control means (2) charges an account on the multimedia call based on the call history information for each connection point stored in said first storing means.

25       13. A multimedia communications system operated in an intelligent network system including a service control

point for collectively managing services provided in a communications network and a plurality of service switching points for processing a call to a terminal unit, wherein

5        each of said service control point and said service switching point comprises:

10        object generating means (1) which assigns a call reference number to a first call request from a terminal unit, generates a parent connection point and a Leg corresponding to communications resources assigned to the first call, generates child connection points and Legs corresponding to communications resources assigned to call requests subsequently generated with said call reference number, and  
15        generates a Call object for integrating a plurality of connection points having said call reference number and the Legs; and

20        communications control means (2) for collectively controlling a plurality of calls based on a relationship between the parent connection point and the child connection points belonging to a same call object.

25        14. The multimedia communications system according to claim 13, wherein

said service control point includes a data base in which an access pointer is provided for sequentially pointing to one of a plurality of information providing centers so that the centers can be equally accessed.

15. The multimedia communications system according to claim 13, wherein

the service switching point transmits to the service control point information specifying a type of images receivable by a terminal unit requesting an image information so that a center capable of broadcasting the image information can be selected by the service control point.

16. A multimedia communications control method for controlling communications using a plurality of media among terminal units, comprising the steps of:

(a) generating an object which defines the relation with other objects and corresponds to communications resources assigned to a multimedia communications request;

(b) generating an integral object for integrating a plurality of said objects; and

(c) integrally controlling communications using

different media by managing a plurality of objects belonging to said integral object based on relations among the plurality of objects.

5 17. The multimedia communications control method according to claim 16, wherein

said step (a) comprises the substeps of:

10 (d) assigning a call identification number identifying a call in response to a first call request from a terminal unit;

(e) generating a parent connection point and a Leg for communications resources assigned to the first call; and

15 (f) generating a child connection point and a Leg for the communications resources of a call in response to a call request which has said call identification number and is generated after the first call request;

said step (b) comprises the substep of:

20 (g) generating a Call object for integrating plural connection points and Legs having said call identification number; and

said step (c) comprises the substep of:

25 (h) integrally controlling a plurality of calls based on relations among connection points

belonging to a same call object.

18. A multimedia communications system as herein-  
before described with reference to any of the  
accompanying drawings.

19. A multimedia communications control method as  
hereinbefore described with reference to any of the  
accompanying drawings.

Patents Act 1977  
 Examiner's report to the Comptroller under Section 17  
 (The search report)

Application number  
 GB 9506461.5

# Relevant Technical Fields

(i) UK Cl (Ed.N) H4K KF42, K0D3, K0T

(ii) Int Cl (Ed.6) H04Q 3/00, 11/04

Search Examiner  
 MR M J BILLING

Date of completion of Search  
 10 MAY 1995

## Databases (see below)

(i) UK Patent Office collections of GB, EP, WO and US patent specifications.

(ii) ONLINE: WPI

Documents considered relevant following a search in respect of Claims :-  
 1 TO 17

## Categories of documents

- |  |  |
|--|--|
| <p>Document indicating lack of novelty or of inventive step.</p> <p>Document indicating lack of inventive step if combined with one or more other documents of the same category.</p> <p>Document indicating technological background and/or state of the art.</p> | <p>P: Document published on or after the declared priority date but before the filing date of the present application.</p> <p>E: Patent document published on or after, but with priority date earlier than, the filing date of the present application.</p> <p>&amp;: Member of the same patent family; corresponding document.</p> |
|--|--|

Category	Identity of document and relevant passages		Relevant to claim(s)
A	GB 2243517 A	(GPT LIMITED) page 2 line 28 to page 4 line 28	1,16
X,P	EP 0641133 A2	(A T & T) Figure 2; column 1 lines 3-16, column 3 line 23 to column 6 line 42. Published 1 March 1995.	1,16 at least
A,P	EP 0631457 A2	(A T & T) column 4 line 46 to column 7 line 38. Published 28 December 1994.	1,16

Databases: The UK Patent Office database comprises classified collections of GB, EP, WO and US patent specifications as outlined periodically in the Official Journal (Patents). The on-line databases considered for search are also listed periodically in the Official Journal (Patents).